



## Features

- The hardened threads with smooth surface finishing avoid galling and help to extend the fitting service life.
- Radius junction design with elbows provides smooth flow path.
- Every fitting is stamped with size, material and heat code.

## Material

Material: 316 Stainless steel

Bar Stock: ASTM A276, ASME SA479, EN 1,4401

Forging: ASTM A182, ASME SA182, EN1.4401

Designator: SS

SIZE	CODE	THREAD (P)	L	F	E	B	Lx	Bx	WORKING PRESSURE
1/8	INS-TFFM02N	NPT	26.4	12.7	4.8	10.4	22.1	9.7	6200 PSI (427 BAR)
1/4	INS-TFFM04N	NPT	29.7	17.5	7.1	15	29.7	14.2	7200 PSI (496 BAR)
3/8	INS-TFFM06N	NPT	36.1	20.6	9.6	15	32	14.2	5600 PSI (385 BAR)
1/2	INS-TFFM08N	NPT	39.6	25.4	11.9	19.8	39.6	19.1	5600 PSI (385 BAR)
3/4	INS-TFFM12N	NPT	48.8	31.8	15.7	20.6	42.4	19.1	5100 PSI (351 BAR)
1	INS-TFFM16N	NPT	48.5	42.9	22.4	25.4	49.3	23.9	6400 PSI (440 BAR)

**\*\* Dimensions subject to change - Please contact us if critical \*\***