



**To work out the inside diameter of the pipe**

1. Multiply the wall thickness by 2
2. Then deduct this number off the OD of the pipe

NERO's range of Press Fit Tube is of welded construction and made to TP304L/W.1.4307 / TP304/W.1.4301 WRAS approved with certification available. Compatible with any brand of fitting/tool

| SIZE (MM) | PRODUCT CODE   | A      | B     | KG /MTR |
|-----------|----------------|--------|-------|---------|
| 15        | PF150.6304W    | 15MM   | 0.6MM | 0.26    |
| 18        | PF180.7304W    | 18MM   | 0.7MM | 0.3     |
| 22        | PF220.7304W    | 22MM   | 0.7MM | 0.37    |
| 28        | PF280.8304W    | 28MM   | 0.8MM | 0.54    |
| 35        | PF351.0304W    | 35MM   | 1MM   | 0.86    |
| 42        | PF421.1304W    | 42MM   | 1.1MM | 1.1     |
| 54        | PF541.2304W    | 54MM   | 1.2MM | 1.59    |
| 76.1      | PF76.1X1.5304W | 76.1MM | 1.5MM | 2.8     |
| 88.9      | PF88.9X1.5304W | 88.9MM | 1.5MM | 3.3     |
| 108       | PF108X1.5304W  | 108MM  | 1.5MM | 4       |

**\*\* Dimensions subject to change - Please contact us if critical \*\***

| Application                                            | Operating temperature | Maximum operating pressure |
|--------------------------------------------------------|-----------------------|----------------------------|
| Hot and cold potable water                             | 0 to 100°C            | 16 BAR                     |
| Heating water                                          | 0 to 100°C            | 16 BAR                     |
| Cooling water without antifreeze agent                 | 0 to 100°C            | 16 BAR                     |
| Cooling water with antifreeze agent                    | -30 to +120°C         | 16 BAR                     |
| Saturated steam                                        | 0 to 120°C            | 2 BAR                      |
| Saturated steam                                        | 5 to 155°C            | 5 BAR                      |
| Service/Treated water                                  | 0 to 100°C            | 16 BAR                     |
| Rainwater/Grey and black water with a pH value of >6.0 | 0 to 100°C            | 16 BAR                     |
| Extinguishing water                                    | 0 to 70°C             | 16 BAR                     |
| Sprinklers                                             | 0 to 70°C             | 16 BAR                     |
| Oils, Fuels and Chemicals                              | Please contact        | Please contact             |