



To work out the inside diameter of the pipe

1. Multiply the wall thickness by 2
2. Then deduct this number off the OD of the pipe

NERO's range of Press fit tube is of welded construction and made to TP316L/W1.4404 / TP316/W1.4401 WRAS approved with certification available. Compatible with any brand of fitting/Tool

SIZE (MM)	PRODUCT CODE	A	B	KG /MTR
15	PF150.6304W	15MM	0.6MM	0.26
18	PF180.7304W	18MM	0.7MM	0.3
22	PF220.7304W	22MM	0.7MM	0.37
28	PF280.8304W	28MM	0.8MM	0.54
35	PF351.0304W	35MM	1MM	0.86
42	PF421.1304W	42MM	1.1MM	1.1
54	PF541.2304W	54MM	1.2MM	1.59
76.1	PF76.1X1.5304W	76.1MM	1.5MM	2.8
88.9	PF88.9X1.5304W	88.9MM	1.5MM	3.3
108	PF108X1.5304W	108MM	1.5MM	4

**** Dimensions subject to change - Please contact us if critical ****

Application	Operating temperature	Maximum operating pressure
Hot and cold potable water	0 to 100°C	16 BAR
Heating water	0 to 100°C	16 BAR
Cooling water without antifreeze agent	0 to 100°C	16 BAR
Cooling water with antifreeze agent	-30 to +120°C	16 BAR
Saturated steam	0 to 120°C	2 BAR
Saturated steam	5 to 155°C	5 BAR
Service/Treated water	0 to 100°C	16 BAR
Rainwater/Grey and black water with a pH value of >6.0	0 to 100°C	16 BAR
Extinguishing water	0 to 70°C	16 BAR
Sprinklers	0 to 70°C	16 BAR
Oils, Fuels and Chemicals	Please contact	Please contact